

CENTRIFUGAL CONCENTRATOR WITH FLOATING BED
Flexicone 110

USERS MANUAL



Attention to consumer Flexicone110!

This manual, combined with the technical description and operating instructions, is a document guaranteed by the manufacturer main parameters and specifications.

Manual is designed to study the concentrator and the principle of its work and sets the operating rules, compliance with which maintains a hub in constant readiness to work.

Taking into account customer feedback the developer is constantly improving product design, so some structural changes in individual units and parts may not be reflected in this data.

PURPOSE

Centrifugal concentrator with floating bed Flexicone110 (hereinafter -concentrator) is designed for high-quality gravity concentration of fine material (sand and alluvial deposits of crushed ore) containing free gold, silver and platinum, in the industrial extraction of small and fine fractions of precious metals and other heavy valuable minerals.

The concentrator can be used:

- 1) In technological research large area samples of mineral raw materials containing precious metals.
- 2) the processing of ore and placer deposits and tailings developments, containing small and micron gold
- 3) in the industrial processing of technogenic raw materials containing precious metals (sand and gravel, aggregates dumps and angry CHP, metallurgical slag, electronic scrap).

concentrator operates indoors or under cover at a positive air temperature. Operating conditions correspond to the performance of IP44

2. SPECIFICATIONS

2.1. A fineness of the processed material, mm - less than 3.

2.2. Performance on hard, kg / h: - 200 *).

2.3. Gold recovery of size,%

+50 microns	96-99
+ 10-50 microns	92-96
+ 3-10 microns,	50-92

2.4. Sand to liquid (ratio S: L) from 1: 4 to 1:12.

(When enrichment placer sands and fine ores S:L – 1:4 ... 1:10, and when finishing roughing concentrates S:L - 1: 8.....1: 12).

2.5. The volume of the resulting concentrate to 1000 ml

2.6. RPM of Bowl 1400

2.7. The frequency of the bowl vibrations /per min 0- 70 Hz

2.8. Power supply 220V (380V + _ 38), frequency (50 + -1) Hz

2.9. Power of motor 150W

2.10. Overall dimensions, mm:

length of not more than 500.

width not more than 350.

height is not more than 370.

2.11 Weight, kg 7.5

*) The maximum output corresponds to the ideal operating conditions (achieved in tests artificial mixtures of quartz sand and granulated ferrosilicon, simulating the density of precious metals), allowing to provide high recovery of small and thin heavy particles. For achieving the best gold recovery results, the feeding rate of material must be reduced according to specific gravity and particle sizes of material.

4.3. The principle of operation of electrical circuit .

The circuit is powered by a single-phase 220volts 50Hz or 110Volts 60Hz

5. SECURITY MEASURES

5.1 Service the concentrator allowed by person familiar with device and past safety training.

5.2. Do not:

- put hands or objects in the area of rotation of the cone when cone rotates ,
- switch ON rotation if the inner cone was not inserted or properly fitted

. 6. MAINTENANCE

6.1. During maintenance the safety requirements are according to section 5 "Safety Precautions" section of this passport.

6.2. At least one time per week, test the state of the cone at fixing points of internal PU cone.

6.3. Every 500 hours of operation concentrator, check the outside cone on wearing of (it is noticeable ring trace from rollers) . If any signs of significant wear , replace the outside bowl.

7. PREPARATION OF THE PRODUCT AND ORDER OF OPERATIONS

Switch ON motor by rotating knob to any of 5 position . (RPM is 1400 in all 5 positions)

Start to feed material with water through the hopper or feed tube to the bottom of the bowl. Try to avoid significant vibration of concentrator. The rotating blades of the impeller is pushing and throw pulp to the sides of the bowl. Under the influence of centrifugal acceleration, grained fraction of the pulp falls into the grooves of bowl, where as a result of fluctuations the loosening material and the segregation of heavy minerals and gold particles formed inside the mineral "bed" with their concentration mainly in the depth of the grooves.

Light mineral particles with the slurry, entrained up flow sludge, rolling through the riffles, are removed from the bowl to the discharging housing and then on the tail pipe outside . In addition to the main pipe, small discharge pipe is located at the bottom of the tube to drain the pulp, accidentally fell into the bottom section.

At the end of cycle (enrichment), stop the motor drive and take out the bowl in the bucket to extract concentrate.

In order to ensure effective concentration and reduce excessive wearing off of parts , selection of the optimal values of bowl speed must be set according feeding rate and material. To achieve maximum recovery , especially when working with heavy concentrate or clay put volume of water feed as much as possible (1m³/hour)

ATTENTION! Control the the drainige bottom pipe during work. If water/pulp comes from pipe, reduce feed rate on hard material and encrease ratio water to hard material .

8. TROUBLESHOOTING AND REMEDIES

1. The motor drive do not turn on or bowl rotation drive motor vibrates or rotating slowly. Rotate bowl by hand. If rotates free , check electrical contacts or cable break. Fix cable and electrical contacts.

If rotates hard – must be sand on crimping rollers . Wash rollers properly with plenty water.

If one of the rollers do not rotate at all, it must be rusted after long storage , make it rotate and replace bearings as soon as convinient for you. **ATTENTION! When finish work and wash concentrator , swith on and let cone to rotate for 1 minute to make it dry and remove all water before storage.**

2. The knock or intermittent noise in the bowl rotation unit. Wearing of main motor bearings and/or cone radial bearings. Wearing of rollers or cone outside

Damaged or overtightened radial bearings. Loose nut of the bearings.

Disassemble and replace worn bearings with new, replace wear of rollers , replace outside cone.